


MCP

COMPACT MCP ASSEMBLY HIGH VOLTAGE FLOATING OPERATION

F13446-11

FEATURES


- High voltage floating operation HV ± 5 kV
- Effective area $\phi 27$ mm
- Time response 1.3 ns FWHM
- Robust MCP
- Compact and thin



OVERVIEW

HAMAMATSU offers NEW compact MCP assembly. This assembly has enough time response characteristic for TOF (Time of Flight) measurement. In addition, HV electrode is able to set the potential from -5 kV to +5 kV. It will be useful to optimize for positive/negative ion or electron detection. Robust MCP in this assembly brings good reliability and low time jitter. In case of high sensitivity is required, large OAR (open area ratio) MCP (funnel type) is also available optionally. Custom modification is also available. Please inform us about your requirements.

OUTPUT WAVEFORM (Typ.)



SPECIFICATIONS

GENERAL

Parameter	Value	Unit
MCP channel diameter	12	μm
Bias angle	12	degree
Effective area	φ27	mm
Number of MCPs	2	—

ELECTRICAL CHARACTERISTICS (Vacuum: 1.3×10^{-4} Pa, at +25 °C)

Parameter	Value	Unit
Gain (Min.) [Ⓐ]	1×10^6	—
Resistance (Typ.) [Ⓐ]	13.4 to 66.6	MΩ
Dark count (Max.) [Ⓐ]	3	s ⁻¹ .cm ⁻²
Pulse width (FWHM) (Typ.)	1.3	ns

NOTE: ⒶHV-BIAS 2.1 kV


MAXIMUM RATINGS

Parameter	Value	Unit
HV-BIAS	2.1	kV
BIAS-SIGNAL	7.1	
SIGNAL-SUBSTRATE	0.0	
Electric potential at each terminal	HV: +5.0/ -5.0 BIAS: +7.1/ -2.9 Signal: GND	kV
Operating vacuum condition	1.3×10^{-4} Ⓑ	Pa
Ambient temperature	0 to +50 °C	°C

NOTE: ⒷBetter vacuum than 1.3×10^{-4} Pa

ⒸNot allowed to be baked.

DIMENSIONAL OUTLINES (Unit: mm)



Subject to local technical requirements and regulations, availability of products included in this promotional material may vary. Please consult with our sales office. Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2020 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K. www.hamamatsu.com

Electron Tube Division

314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation; 360 Foothill Road, Bridgewater, NJ 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com

Germany: Hamamatsu Photonics Deutschland GmbH; Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8 E-mail: info@hamamatsu.de

France: Hamamatsu Photonics France S.A.R.L.; 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: infos@hamamatsu.fr

United Kingdom: Hamamatsu Photonics UK Limited; 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777 E-mail: info@hamamatsu.co.uk

North Europe: Hamamatsu Photonics Norden AB; Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01 E-mail: info@hamamatsu.se

Italy: Hamamatsu Photonics Italia S.r.l.; Strada della Moia, 1 int. 6, 20020 Aresè (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41 E-mail: info@hamamatsu.it

China: Hamamatsu Photonics (China) Co., Ltd.; 1201 Tower B, Jiaming Center, 27 Dongsanhuan Belu, Chaoyang District, 100020 Beijing, P.R. China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866 E-mail: hpc@hamamatsu.com.cn

Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.; 8F-3, No.158, Section 2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)3-659-0080, Fax: (886)3-659-0081 E-mail: info@hamamatsu.com.tw

TMCP1043E04
OCT. 2020 IP