

# Mini-spectrometers



[ **TG series** ]

C9913GC

C9914GB

**For near IR, integrating optical system,  
image sensor and circuit**

Hamamatsu TG series mini-spectrometers C9913GC, C9914GB are polychromators integrated with optical elements and an image sensor. Light to be measured is guided into the entrance port of TG series through an optical fiber and the spectrum measured with the built-in image sensor is output from the USB port to a PC for data acquisition. The C9913GC and C9914GB allow accurate measurement with low noise by cooling the image sensor. The C9913GC and C9914GB come supplied with evaluation software that allows setting measurement conditions, acquiring and saving data, and displaying graphs. Original measurement software can be designed on an end-user's side as DLL's function specification is disclosed.

## Features

- High throughput due to transmission grating made of quartz
- Highly accurate optical characteristics
- Low noise
- Compact design for easy assembly
- Wavelength conversion factor\*1 is recorded in internal memory

\*1: A conversion factor for converting the image sensor pixel number into a wavelength is recorded in the module. A calculation factor for converting the A/D converted count into the input light level is not provided.

## Applications

- Water content measurement
- Component analysis in food, agriculture fields, etc.
- Process control for chemical products
- Plastic sorting

## Optical characteristics

Parameter	TG-cooled NIR-I		TG-cooled NIR-II		Unit
	C9913GC		C9914GB		
Spectral response range	900 to 1700		1100 to 2200		nm
Spectral resolution (FWHM)*2	Typ.	5	6		nm
	Max.	7	8		
Wavelength reproducibility*3	-0.2 to +0.2		-0.4 to +0.4		nm
Wavelength temperature dependence	-0.02 to +0.02		-0.04 to +0.04		nm/°C
Spectral stray light*2 *4	-35 max.				dB

\*2: Depends on the slit opening. Values were measured with the slit listed in the table "Structure".

\*3: Measured under constant light input conditions

\*4: When monochromatic light of the following wavelengths is input, spectral stray light is defined as the ratio of the count measured at the input wavelength, to the count measured in a region of the input wavelength  $\pm 40$  nm.

C9913GC: 1300 nm, C9914GB: 1650 nm

## Electrical characteristics

Parameter	C9913GC	C9914GB	Unit
A/D conversion	16		bit
Integration time	5 to 10000	5 to 1000	ms
Interface	USB 1.1		-
Current consumption of USB bus power	250 max.		mA

**Structure**

Parameter	C9913GC	C9914GB	Unit
Dimensions (W × D × H)	142 × 218 × 82		mm
Weight	1700		g
Image sensor	TE-cooled type InGaAs linear image sensor (G9204-512S)	TE-cooled type InGaAs linear image sensor	-
Number of pixels*5	512	256	pixels
Slit*6 (H × V)	70 × 500		μm
NA*7	0.22		-
Connector for optical fiber	SMA905D		-
Current consumption for cooling element (+5 V)*8	1.8 max.	2.8 max.	A
Current consumption for cooling fan (+12 V)*8	0.2 max.		A

\*5: No defective pixel (when inspecting at low gain). Defective pixels are those whose electrical and optical characteristics do not meet our specifications.

\*6: Entrance slit aperture size

\*7: Numeric aperture (solid angle)

\*8: Maximum value in steady state. Note that inrush current flows at start-up.

The connector for connection to cooling element and cooling fan power supply is attached.

**Absolute maximum ratings**

Parameter	C9913GC	C9914GB	Unit
Operating temperature*9	+5 to +35 (+5 to +30*10)		°C
Storage temperature*9	-20 to +70		°C


\*9: No dew condensation

When there is a temperature difference between a product and the surrounding area in high humidity environment, dew condensation may occur on the product surface. Dew condensation on the product may cause deterioration in characteristics and reliability.

\*10: For controllable cooling temperature

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

**Spectral resolution vs. wavelength (typical example)**




KACCB0263EA

KACCB0264EA


**Linearity (typical example)**

C9913GC



KACCB0251EB

C9914GB




KACCB0252EB

A/D output is the output with dark output is subtracted when light is input. The difference between the ideal value and typical example contains a measurement error. The smaller the A/D output, the larger the measurement error.


**Dark output vs. ambient temperature (typical example)**

C9913GC



KACCB0254EA

C9914GB




KACCB0255EA

A/D output is the sum of the sensor and circuit offset outputs and the sensor dark output.

**Optical component layout**


TG series mini-spectrometers use a transmission holographic grating made of quartz and precision optical components arranged on a rugged optical base, making it possible to deliver high throughput and highly accurate optical characteristics.



KACCC0256EA

**Connection example (transmission light measurement)**

Light to be measured is guided into the entrance port of TG series through an optical fiber and the spectrum measured with the built-in image sensor is output through the USB port to a PC for data acquisition. There are no moving parts inside the unit so stable measurements are obtained at all times. An optical fiber that guides light input from external sources allows a flexible measurement setup.




\* External power supply should be prepared by the user.

KACCC0370EE

### ❑ Evaluation software package (supplied with unit)

Installing the evaluation software package (Spec Evaluation.exe)\*11 into your PC allows running the following basic tasks:

- Measurement data acquisition and save
- Measurement condition setup
- Module information acquisition  
(wavelength conversion factor, polychromator type, etc.)
- Graphic display
- Arithmetic operation
  - Pixel number to wavelength conversion
  - Comparison calculation with reference data  
(transmittance, reflectance)
  - Dark subtraction
  - Gaussian approximation  
(peak position and count, FWHM)



Note:

- Two or more mini-spectrometers can be connected and used with one PC simultaneously.
- The external trigger input function does not work with the evaluation software. If using an external trigger input or designing original application software, the user software must be configured to support that function.

\*11: Compatible OS: Microsoft Windows 8.1 Professional (32-bit, 64-bit)  
Microsoft Windows 10 Professional (32-bit, 64-bit)

DLL for controlling hardware is also provided.

You can develop your own measurement programs by using a following software development environment.

Microsoft Visual Studio® 2008 (SP1) Visual C++®


Microsoft Visual Studio 2008 (SP1) Visual Basic®

Note: Microsoft, Windows, Visual Studio, Visual C++ and Visual Basic are either registered trademarks or trademarks of Microsoft Corporation in the United States and other countries.

### ❑ Measurement example

Film thickness measurement (white light interferometry)

Thickness of 10  $\mu\text{m}$  thick food wrapping film (polyvinylidene chloride) was measured.




Note:

Principle of film thickness measurement:

In film thickness measurement utilizing white light interferometry, an interference spectrum resulting from internal reflections between the front and back surfaces of a film is obtained.

The film thickness can then be determined by calculation from the spectral peak count, wavelength range, refractive index of film and incident light angle.

### Dimensional outlines (unit: mm)



Tolerance unless otherwise noted:  $\pm 1.0$   
Weight: 1.7 kg

KACCA0158EE

### Accessories

- USB cable
- Dedicated software (evaluation software, sample software, DLL)
- External power supply connector [made by LEMO S.A.: FGG0B304CLAD56 (only available in C9913GC and C9914GB)]

### Options (sold separately)

- Optical fiber for light input

Type no.	Product name	Core diameter ( $\mu\text{m}$ )	Specification
A15363-01	Fiber for visible/near infrared range	600	NA=0.22, length 1.5 m, connectorized SMA905D at both ends

## Related information

[http://www.hamamatsu.com/sp/ssd/doc\\_en.html](http://www.hamamatsu.com/sp/ssd/doc_en.html)

### ■ Precautions

- Disclaimer
- Mini-spectrometers

### ■ Technical information

- Mini-spectrometers

Information described in this material is current as of September 2020.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

# HAMAMATSU

[www.hamamatsu.com](http://www.hamamatsu.com)

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81)53-434-3311, Fax: (81)53-434-5184

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, N.J. 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218, E-mail: [usa@hamamatsu.com](mailto:usa@hamamatsu.com)

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8, E-mail: [info@hamamatsu.de](mailto:info@hamamatsu.de)

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10, E-mail: [infos@hamamatsu.fr](mailto:infos@hamamatsu.fr)

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777, E-mail: [info@hamamatsu.co.uk](mailto:info@hamamatsu.co.uk)

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01, E-mail: [info@hamamatsu.se](mailto:info@hamamatsu.se)

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41, E-mail: [info@hamamatsu.it](mailto:info@hamamatsu.it)

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, 27 Dongsanhuan Beilu, Chaoyang District, 100020 Beijing, P.R.China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866, E-mail: [hpc@hamamatsu.com.cn](mailto:hpc@hamamatsu.com.cn)

Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.: 8F-3, No. 158, Section2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)3-659-0080, Fax: (886)3-659-0081, E-mail: [info@hamamatsu.com.tw](mailto:info@hamamatsu.com.tw)