

The S13954-01CT is a photodiode that has an extremely wide operating and storage temperature range (-40 to +125 °C). A high-speed response (230 MHz typ.) is achieved.

Features

Applications

Laser power monitoring, etc.

- High-speed response: 230 MHz
- (VR=3 V, RL=50 Ω, λ=650 nm, -3 dB)
- Operating/storage temperature: -40 to +125 °C
- Surface mount type, small and thin leadless package
- Photosensitive area: φ1.5 mm
- Suitable for lead-free solder reflow

Structure

Parameter	Value	Unit
Photosensitive area	φ1.5	mm
Package	Epoxy/Glass	-
Window material	Silicone resin	-

- Absolute maximum ratings

Parameter	Symbol	Value	Unit
Reverse voltage	VR max.	10	V
Operating temperature	Topr	-40 to +125	°C
Storage temperature	Tstg	-40 to +125	°C
Reflow soldering conditions*1	Tsol	Peak temperature: 260 °C, twice (see P.5)	-

*1: JEDEC level 4

Note: Exceeding the absolute maximum ratings even momentarily may cause a drop in product quality. Always be sure to use the product within the absolute maximum ratings.

Electrical and optical characterisitcs (Ta=25 °C)

Parameter	Symbol	Condition	Min.	Тур.	Max.	Unit
Spectral response range	λ		-	320 to 1000	-	nm
Peak sensitivity wavelength	λр		-	780	-	nm
Photosensitivity	S	λ=λp	0.4	0.5	-	A/W
Dark current	Id	VR=3 V	-	0.01	1	nA
Temperature coefficient of ID	TCID	VR=3 V	-	1.12	-	times/°C
Cutoff frequency	tr	VR=3 V, RL=50 Ω λ=650 nm, -3 dB	125	230	-	MHz
Terminal capacitance	Ct	VR=3 V, f=1 MHz	-	13	25	pF

Spectral response





PINB0424EA



Dark current vs. reverse voltage

Terminal capacitance vs. reverse voltage



Photosensitivity temperature characteristics





Frequency characteristics



(Typ. Ta=25 °C, light source: tungsten lamp)



KPINB0428EA



Si PIN photodiode

Dimensional outline (unit: mm)



Recommended land pattern



Standard packing specifications

Reel (conforms to JEITA ET-7200)

Dimensions	Hub diameter	Tape width	Material	Electrostatic characteristics
254 mm	100 mm	12 mm	Polystyrene	Conductive

Embossed tape (unit: mm, material: polystyrene, conductive)



Packing quantity 2000 pcs/reel

Packing type Reel and desiccant in moisture-proof packaging (vacuum-sealed)
HAMAMATSU



Recommended reflow soldering conditions

Time

KPINB0385EB

- . This product supports lead-free soldering. After unpacking, store it in an environment at a temperature of 30 °C or less and a humidity of 60% or less, and perform soldering within 72 hours.
- The effect that the product receives during reflow soldering varies depending on the circuit board and reflow oven that are used. Before actual reflow soldering, check for any problems by testing out the reflow soldering methods in advance.

Related information

www.hamamatsu.com/sp/ssd/doc_en.html

- Precautions
- Disclaimer
- Surface mount type products
- Technical information
- · Si photodiode / Application circuit examples

Information described in this material is current as of January 2021.

Product specifications are subject to change without prior notice due to improvements or other reasons. This document has been carefully prepared and the information contained is believed to be accurate. In rare cases, however, there may be inaccuracies such as text errors. Before using these products, always contact us for the delivery specification sheet to check the latest specifications.

The product warranty is valid for one year after delivery and is limited to product repair or replacement for defects discovered and reported to us within that one year period. However, even if within the warranty period we accept absolutely no liability for any loss caused by natural disasters or improper product use. Copying or reprinting the contents described in this material in whole or in part is prohibited without our prior permission.

MAMATSU

www.hamamatsu.com

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81)53-434-3311, Fax: (81)53-434-5184 U.S.A: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, NJ. 08807, U.S.A., Telephone: (1)908-231-960, Fax: (1)908-231-1218, E-mail: usa@hamamatsu.com Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8, E-mail: info@hamamatsu.de France: Hamamatsu Photonics France S.A.R.L: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10, E-mail: info@hamamatsu.de Inited Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 18W, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777, E-mail: info@hamamatsu.co.uk

Neurophysical international foreign and the second seco North Europe: Ha Italv: Ha