

NEW

ORCA[®]-Flash4.0LT3

Digital CMOS camera C11440-42U40



The ORCA[®]-Flash4.0 LT3 is a new scientific CMOS camera for fluorescence imaging, which has been improved from the ORCA[®]-Flash 4.0 released in 2011.


It is equipped with a high level of performance required for fluorescence imaging such as life science applications, and can be used not only for basic research applications but also for integration into various types of equipment.

High S/N equivalent or better than BSI camera

The graph below compares the readout noise distribution with the Gen II BSI camera* and shows that the ORCA[®]-Flash4.0 LT3 has more pixels with smaller readout noise.

With a low readout noise of 1.5 electrons rms, the ORCA[®]-Flash4.0 LT3 delivers high S/N comparable to or better than a BSI camera, especially in the low light range. This performance can be demonstrated in high quality multidimensional imaging, as typified by long time-lapse imaging with low excitation light with low phototoxicity and photobleaching.

* BSI camera: Back-side illuminated camera



Features

- Low readout noise (Standard scan): 1.5 electrons rms, 0.9 electrons median
- High speed readout (Rapid rolling, Full resolution): 40 frames/s
- Large field of view: 13.312 mm (H)×13.312 mm (V)
- High resolution: 2048 (H)×2048 (V)
- High quantum efficiency: 82 % (Peak QE)

Applications

- Time-lapse imaging
- Multidimensional imaging
- Ca²⁺ imaging
- DNA chip reading


High speed readout

The ORCA[®]-Flash4.0 LT3 is capable of 40 frames/second readout, which is even faster than the conventional ORCA[®]-Flash4.0 LT+ (30 frames/second).

This is useful for applications which requires real time measurement with high temporal resolution.

Large field of view

The wide field of view of 13.312 mm (H) × 13.312 mm (V) allows more information to be obtained in a single shot. This contributes to higher throughput in experiments such as DNA chip reading.




Sample:
FluoCells™ Prepared slide #3 mouse kidney section
Fluorescence probes:
DAPI, AF488 WGA, AF568 phalloidin
Objective lens:
Plan Apo 20×/0.75

Specifications

Product number		C11440-42U40	
Imaging device		Scientific CMOS image sensor	
Effective number of pixels		2048 (H) × 2048 (V)	
Pixel size		6.5 μm (H) × 6.5 μm (V)	
Effective area		13.312 mm (H) × 13.312 mm (V)	
Full well capacity (typ.)		30 000 electrons	
Dynamic range (typ.)		33 000: 1 *1 20 000: 1 *2	
Cooling method		Forced-air cooled, peltier cooling	
Cooling temperature	Forced-air cooled (FAN speed: Fast ambient temperature: +10 °C to +30 °C)	+10 °C	
Frame rate at full resolution	Rapid rolling	40 frames/s	
	Standard scan	30 frames/s	
Readout noise (typ.)	Rapid rolling	1.9 electrons rms / 1.3 electrons median	
	Standard scan	1.5 electrons rms / 0.9 electrons median	
Dark current (typ.)	Cooling temperature: +10 °C	0.6 electrons/pixel/s	
Digital output		16 bit	
Exposure time	Internal trigger mode *3	Rapid rolling	1 ms to 10 s
		Standard scan	3 ms to 10 s
	Internal trigger mode with sub-array readout	Rapid rolling	40 μs to 10 s
		Standard scan	129.99 μs to 10 s
External trigger input mode		Edge trigger, Global reset edge trigger, Level trigger, Global reset level trigger, Synchronous readout trigger, Start trigger	
Trigger delay function		0 s to 10 s in 1 μs steps	
Trigger input connector		SMA	
Trigger output		3 programmable timing outputs, Trigger ready output, Global exposure timing output, Low output, High output	
Trigger output connector		SMA	
Binning		2×2, 4×4	
Sub-array		Yes	
Interface		USB 3.1 Gen 1	
Lens mount		C-mount	
Power supply		AC 100 V to AC 240 V, 50 Hz / 60 Hz	
Power consumption		Approx. 75 VA	
Ambient operating temperature	FAN speed: Fast	0 °C to +40 °C	
Ambient operating humidity		30 % to 80 % (With no condensation)	
Ambient storage temperature		-10 °C to +50 °C	
Ambient storage humidity		90 % Max. (With no condensation)	

*1 Calculated from the ratio of the full well capacity and the readout noise (median) in standard scan
 *2 Calculated from the ratio of the full well capacity and the readout noise (rms) in standard scan
 *3 Minimum exposure time in internal trigger mode varies depending on sub-array size and position.

Spectral response



ORCA is registered trademark of Hamamatsu Photonics K.K. (China, France, Germany, Japan, U.K., U.S.A.)

Product and software package names noted in this documentation are trademarks or registered trademarks of their respective manufacturers.

- Subject to local technical requirements and regulations, availability of products included in this promotional material may vary. Please consult your local sales representative.
- Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions.
- Specifications and external appearance are subject to change without notice.

© 2023 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K. www.hamamatsu.com

Systems Division

812 Joko-cho, Higashi-ku, Hamamatsu City, 431-3196, Japan, Telephone: (81)53-431-0124, Fax: (81)53-433-8031, E-mail: export@sys.hpk.co.jp

U.S.A.: HAMAMATSU CORPORATION: 360 Foothill Road, Bridgewater, NJ 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218

Germany: HAMAMATSU PHOTONICS DEUTSCHLAND GMBH: Arzbergerstr. 10, 82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8 E-mail: info@hamamatsu.de

France: HAMAMATSU PHOTONICS FRANCE S.A.R.L.: 19 Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: infos@hamamatsu.fr

United Kingdom: HAMAMATSU PHOTONICS UK LIMITED: 2 Howard Court, 10 Twin Road, Welwyn Garden City, Hertfordshire, AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777 E-mail: info@hamamatsu.co.uk


North Europe: HAMAMATSU PHOTONICS NORDEN AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01 E-mail: info@hamamatsu.se

Italy: HAMAMATSU PHOTONICS ITALIA S.R.L.: Strada della Moia, 1 int. 6, 20044 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41 E-mail: info@hamamatsu.it

China: HAMAMATSU PHOTONICS (CHINA) CO., LTD.: 1201 Tower B, Jiaming Center, 27 Dongsanjuan Beilu, Chaoyang District, 100020 Beijing, P.R. China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2866 E-mail: hpc@hamamatsu.com.cn

Taiwan: HAMAMATSU PHOTONICS TAIWAN CO., LTD.: 8F-3, No.158, Section 2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C., Telephone: (886)3-659-0080, Fax: (886)3-659-0081 E-mail: info@hamamatsu.com.tw

System configuration



Options

Product number	Product name
M9982-26	Frame grabber board with USB 3.0 A-MicroB 3m Cable
A12046-03	USB 3.0 cable A-MicroB 3 m
A12106-05	External trigger cable SMA-BNC 5 m
A12107-05	External trigger cable SMA-SMA 5 m
A11186-01	Base plate common for Flash4.0 chassis

Dimensional outlines (Unit: mm)

