

Metal Package PMT

Photon Counting Head H11890 Series



The H11890 series is a compact photon counting head consisting of a metal package photomultiplier tube along with a high speed photon counting circuit and a high-voltage power supply unit. The high voltage supply for the photomultiplier tube and the discriminator level are preset to optimum values, allowing photon counting measurement by just connecting to a PC.

Photon counting measurement data transfer, counter gate time and other necessary adjustments are controlled by commands from the PC through the USB interface.

Since the H11890 series performs linearity correction by the internal MPU, it provides excellent count linearity within a range of -10 % at $2 \times 10^7 \text{ s}^{-1}$.

Product Variations

Type No.	Spectral response	Features
H11890-110	230 nm to 700 nm	Super bialkali photocathode, high sensitivity in visible range.
H11890-210	230 nm to 700 nm	Ultra bialkali photocathode, high sensitivity in visible range.
H11890-01	230 nm to 870 nm	Multialkali photocathode, for UV to near IR range.

This product can't be used at vacuum environment or reduced pressure environment.

Specifications

(at +25 °C)

Parameter		H11890-110	H11890-210	H11890-01	Unit	
Input voltage		USB bus power			—	
Max. input current		50			mA	
Effective area		$\phi 8$			mm	
Peak sensitivity wavelength		400			nm	
Spectral response range		230 to 700	230 to 700	230 to 870	nm	
Count sensitivity	Typ.	300 nm	3.7×10^5	3.9×10^5	2.7×10^5	$\text{s}^{-1} \cdot \text{pW}^{-1}$
		400 nm	4.9×10^5	6.1×10^5	3.6×10^5	
		500 nm	3.7×10^5	4.6×10^5	2.8×10^5	
		600 nm	1.1×10^5	1.3×10^5	2.0×10^5	
		700 nm	7.7×10^3	9.1×10^3	1.2×10^5	
		800 nm	—	—	3.0×10^4	
Count linearity ^{*1}		5.0×10^6 2.0×10^7 (with function of linearity correction)			s^{-1}	
Dark count ^{*2}	Typ.	50	50	600	s^{-1}	
	Max.	100	100	1000	s^{-1}	
Pulse-pair resolution		20			ns	
Counter gate time		1 to 10 000 (PC control)			ms	
Counter method		Double counter			—	
Count date		4 byte (MSB: Overlight detection bit)			—	
Interface		USB 2.0			—	
Compatible OS		Windows® 10 Pro			—	
Operating ambient temperature ^{*3}		+5 to +40			°C	
Storage temperature ^{*3}		-20 to +50			°C	
Weight		54			g	



*1: Random pulse, at 10 % count loss.

*2: After 30 minutes storage in darkness at plateau voltage.


*3: No condensation

* Supplied: CD-ROM (containing instruction manual, device driver, DLL, sample software, C++ sample code, Labview sample code), USB cable (1.5 m)
Windows® is a registered trademark of Microsoft Corporation in the United States and/or other countries.


Characteristics (Count sensitivity, Dark count)



●Count rate linearity and over light detection output



●Count rate linearity correction




Correction Formula

$$N = \frac{M}{1 - Mt}$$

N: Real Count Rate (s⁻¹)
M: Measured Count Rate (s⁻¹)
t: Pulse Pair Resolution (s)


Block diagram




Options

(Optical fiber adapter) (Unit: mm)


E5776 (FC type)



E5776-51 (SMA type)



Dimensional outlines (Unit: mm)



Electron Tube Division

314-5, Shimokanzo, Iwata City, Shizuoka Pref., 438-0193, Japan, Telephone: (81)539/62-5248, Fax: (81)539/62-2205

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, Bridgewater, NJ 08807, U.S.A., Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-265-8 E-mail: info@hamamatsu.de

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: (33)1 69 53 71 00, Fax: (33)1 69 53 71 10 E-mail: infos@hamamatsu.fr

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, UK, Telephone: (44)1707-294888, Fax: (44)1707-325777 E-mail: info@hamamatsu.co.uk

North Europe: Hamamatsu Photonics Norden AB: Torshamnsgatan 35 16440 Kista, Sweden, Telephone: (46)8-509 031 00, Fax: (46)8-509 031 01 E-mail: info@hamamatsu.se

Italy: Hamamatsu Photonics Italia S.r.l.: Strada della Moia, 1 int. 6, 20020 Arese (Milano), Italy, Telephone: (39)02-93 58 17 33, Fax: (39)02-93 58 17 41 E-mail: info@hamamatsu.it

China: Hamamatsu Photonics (China) Co., Ltd.: 1201 Tower B, Jiaming Center, 27 Dongsanhuan Beilu, Chaoyang District, 100020 Beijing, P.R. China, Telephone: (86)10-6586-6006, Fax: (86)10-6586-2806 E-mail: hpc@hamamatsu.com.cn

Taiwan: Hamamatsu Photonics Taiwan Co., Ltd.: 8F-3, No.158, Section 2, Gongdao 5th Road, East District, Hsinchu, 300, Taiwan R.O.C. Telephone: (886)3-659-0080, Fax: (886)3-659-0081 E-mail: info@hamamatsu.com.tw